

Rhenocoll Universalpflege R9, care product, water-based, ecologically friendly
Art. No.: A 4525

Application area: Rhenocoll Universalpflege R9 cleans and cares all sealed and oiled or waxed wood, parquet and cork surfaces as well as gyms. It reduces the slip resistance according to DIN 51130 and 51097. Also to be used for other floors such as PVC, linoleum and rubber floors. For professional use.

Properties: Slip resistant, water-based, hard-wearing. According to DIN 18032, part 2. Does not build up care medial layer (no gloss increase).

VOC directive 2010: not applicable.

Cleaning of ground and final construction:

At cleaning of final construction the laying activities are being removed because of dirt such as dust and adhesive residue. A basic cleaning is required when shoe prints, excessive soiling and old care agent layering or possible film of wax must be removed.

Regular maintenance cleaning:

First remove dirt and sand with a dry cloth or brush of the vacuum cleaner because both act like sanding paper. Afterwards add ca. 50 – 100 ml Rhenocoll Universalpflege R9 (1 cup) according to use into a bucket with 10 liter clean water and wipe the surface with a cloth. The rest of the moisture dries by itself. Polishing is not required.

Important hints:

- Work with 2 buckets: one for the clean Rhenocoll Universalpflege R9, the other one to wring out the cloth.
- Do not mix Rhenocoll Universalpflege R9 with any other care and cleaning product! In connection of any other care product with a Rhenocoll Universalpflege R9 treatment leads to faults on the surface.
- As long as Rhenocoll Universalpflege R9 film damply shines do not step on or wipe with a cloth.

General hints:

Principally do not flood the floor when cleaning because damage through swelling of substrate (for instance wood) can occur. Always care damp-cloth! The more the freshly sealed, oiled or waxed floor is spared the longer the life duration opaque lacquer. Full load after fully hardening of lacquer film (depending on climatic conditions and lacquer system).

Room temperature must be at least 20° C , 55% humidity for conservation of value especially of wooden and parquet floor and for well-being of human being. Lower humidity than the recommended humidity gap formation on parquet can occur. If necessary use humidifier.

Storage:

Store and transport in original container not under +6°C. Keep firmly closed. Storable in the unopened, original container for 6 months. Opened container must be closed firmly and must be used up soon.

Supply units:

1 liter can
5 liter can

Labelling:

VbF: not applicable
GefStoffV: no labeling required
GGVSE: no labeling required
UBA = 4894-001

Service:

Our service team for application technology is available to you at any time without obligation.

Phone: ++49 (0)6384 99 38 - 0
Fax: ++49 (0)6384 99 38 - 112
Email: info@rhenocoll.de

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case.

With the release of this Technical Data Sheet all previous versions become obsolete.