

**AQUA - Glaslack G12 Top**

**Art. No.: A 4595**

Top coat varnish, colourless

Environmentally friendly, water-based varnish

**Degree of gloss:** Silky matt

**Application area:** Colourless top coat varnish for the treatment of glass surfaces which have already been coated with a decorative glass varnish (G1, G2, G3). The scratch resistance will be significantly increased by using the glass varnish G12. Suitable for all interior glass surfaces in connection with furniture, windows and doors, room dividers and built-in components.

**Features:** One component varnish, no pot life, no waste. Suitable as a top coat varnish onto decorative glass varnish. This varnish is used if the scratch resistance of the decorative varnish is to be increased. Spreads well. Abrasion and scratch resistant. Excellent adhesion according to DIN EN ISO 2409 (GT = 0), resistant against water and common cleaning products. No yellowing. AQUA Glaslack is to be applied in one layer, although follow-up coats are possible.

**Processing instructions:** Shake or stir product well before use. AQUA Glaslack is ready to use without dilution.

**Application:** Spraying.

**Nozzle size:** 1.8 – 2 mm nozzle with 2.5 - 3 bar with a gravity cup spray gun.

**Drying:** At 20°C and 65% relative humidity: dust dry after 30 min., touch dry after 50 min. For complete drying leave over night.

**Application amount:** max. 100g/m<sup>2</sup> per spraying step.

**Dilution:** With water.

**Cleaning:** With water, immediately after use. Dried varnish can be removed with universal thinner or acetone.

**Processing:** The already coated glass surface must be dry and free from dust and grease. Apply Glaslack G12 evenly. The coating with Glaslack G12-Top increased the scratch resistance.

**Cleaning of the coated surface:** With neutral household cleaner (do not use ethyl alcohol cleaner).

**Storage:** Store or transport in original container not below +7°C, and not above +30°C for any length of time; close firmly.

**Supply unit:**

1 litre can  
5 litre pail  
20 litre pail

**Disposal:** Not fully hardened or completely dried out left over product are to be disposed of as special waste (AVV waste code no. 030202). Recycle empty containers.

**Ecology:** Left over varnish not to be disposed of into waters. The product is hazardous to water according to the German Water Act §19. WGK = 2 (self-classification).

**VOC directives:** Cat. I / Base Wb / max value 140 g/L / IST value 99 g/L.

**Labelling:**

VbF: n/a  
GefStoffV: no labelling required  
GGVS: no labelling required

**Safety information:** Keep locked up and out of reach of children. Avoid contact with eyes. In case of contact with eyes, wash immediately with plenty of water.

**Service:**

Our service team for application technology is available to you at any time without obligation.

**Phone:** ++49 (0)6384 99 38 - 0  
**Fax:** ++49 (0)6384 99 38 - 112  
**Email:** [info@rhenocoll.de](mailto:info@rhenocoll.de)

The information given within is without obligation and is based on practical experience as well as on experiments which we have carried out and are not attribute guaranties in the sense of the newest BGH legal requirements. We recommend that in any case users carry out their own tests since we have no influence over the large diversity of materials and their processing. No liability for the manufacturer can be derived from the contents of this data sheet. Statements going beyond or deviating from the contents of this data sheet require the written confirmation of the company headquarters. Our General Terms & Conditions apply in any case.

With the release of this Technical Data Sheet all previous versions become obsolete.